



## Member of SAAMI SPECIFICATION SHEET BV 5.56-1N

---

**Manufacture:** ProGrade Ammo Group LLC d/b/a BVAC.

**Bullet:** 55 grain Full Metal Jacket

**Primer:** Small Rifle - Non-corrosive, Boxer Type

**Primer Sealant:** AT REQUEST

**Case Mouth Sealant:** AT REQUEST

**Propellant:** - Ball clean burning.

**Propellant Detection:** 100% mechanical and/or electrical detection of propellant levels within the cartridge.

**Cartridge Case:** Boxer primed LC 5.56 New

**Headstamp:** Case manufacturer's symbol and cartridge designation.

**Velocity:** 3100 fps in SAAMI standard test barrel.

**Muzzle Energy:** 1281 ft-lbs.

**Chamber Pressure:** 47,500 CUP by SAAMI recommended test equipment.

**Bullet Pull:** 20 lbs (minimum/individual).

**Accuracy:** Average mean radius = 1 MOA

**Inspection:** 100% visual inspection of finished cartridges prior to packaging.

**b. Packaging:**

Inner: Fiberboard cartons.

Outer: Corrugated cardboard construction.

**c. Markings:**

Inner Packing: Standard Nomenclature.  
Lot Number.  
Manufacturer.

Outer Packing: Standard Nomenclature.  
Lot Number.  
Manufacturer.